

Xerox® ColorQube® 8700

Color Multifunction Printer

The ColorQube 8700 Multifunction Printer is built on Xerox® ConnectKey® Technology. For more information, go to www.connectkey.com.



ColorQube 8700S
A full-featured multifunction printer with automatic 2-sided print/copy/scan capabilities



ColorQube 8700X
All of the features of the 8700S plus faxing capabilities



ColorQube 8700XF
Adds (2) 525-sheet paper trays, 1,800-sheet High-Capacity Feeder and a 650-sheet Finisher

| System Specifications | | ColorQube 8700S | ColorQube 8700X | ColorQube 8700XF |
|---|---------------|--|---|------------------|
| One-sided Speed | | Color and Black-and-white | | |
| Fast Color Mode ¹ : | | 44 ppm 8.5 x 11 in. / A4 (210 x 297 mm) / 18 ppm 8.5 x 14 in. | | |
| Standard Mode ¹ : | | 30 ppm 8.5 x 11 in. / A4 (210 x 297 mm) / 15 ppm 8.5 x 14 in. | | |
| Enhanced Mode (Default): | | 19 ppm 8.5 x 11 in. / A4 (210 x 297 mm) / 11 ppm 8.5 x 14 in. | | |
| High Resolution: | | 6 ppm 8.5 x 11 in. / A4 (210 x 297 mm) / 5 ppm 8.5 x 14 in. | | |
| Two-sided Speed | | Color and Black-and-white | | |
| Fast Color Mode ¹ : | | 30 ppm 8.5 x 11 in. / A4 (210 x 297 mm) | | |
| Standard Mode ¹ : | | 25 ppm 8.5 x 11 in. / A4 (210 x 297 mm) | | |
| Enhanced Mode (Default): | | 18 ppm 8.5 x 11 in. / A4 (210 x 297 mm) | | |
| High Resolution: | | 6 ppm 8.5 x 11 in. / A4 (210 x 297 mm) | | |
| Monthly Duty Cycle² | | Up to 120,000 pages | | |
| Recommended Average Monthly Print Volume³ | | 1,000 to 6,000 pages | | |
| Hard Drive / Processor / Memory | | Minimum 80 GB / 1.33 GHz Dual-core / 1 GB | | |
| Connectivity | | 10/100/1000Base-T Ethernet, High-Speed USB 2.0 Direct Print, Optional Wi-Fi (with Xerox® USB Wireless Adapter) | | |
| Controller Features | | Unified Address Book, Remote Control Panel, Online Support (accessed from the user interface and print driver), Configuration Cloning | | |
| Print and Copy | | | | |
| Print and Copy Resolution | | Print: Up to Xerox® 2400 FinePoint®; Copy: Up to 600 x 600 dpi | | |
| First-print-out Time (as fast as) | | Print: 8.5 seconds color; Copy: 16 seconds color and black-and-white | | |
| Page Description Languages | | Adobe® PostScript® 3™, PDF, PCL® 5c / PCL 6, XML Paper Specification (XPS®) | | |
| Print Features | | Print from USB, Earth Smart Driver Settings, Job Identification, Booklet Creation, Store and Recall Driver Settings, Bi-directional Status, Scaling, Job Monitoring, Color By Words, Print Around, Sample Set, Smart Duplex, Automatic Two-sided, Automatic Color Correction, Custom Color Correction, Spot Color Matching | | |
| Mobile Printing and Apps | Standard | Apple® AirPrint™, Mopria® certified | | |
| | Free Download | Xerox® Mobile Link App, Xerox® Print Service Plug-in for Android™ | | |
| | Optional | Xerox® Mobile Print, Xerox® Mobile Print Cloud | | |
| Scan | | | | |
| Standard Features | | Destinations: Scan to Mailbox; Scan to USB, Scan to Email, Scan to Network; File Formats: PDF, PDF/A, XPS, JPEG, TIFF; Convenience Features: Scan to Home, Single Touch Scan, Searchable PDF, Single/Multi-Page PDF / XPS / TIFF, Encrypted / Password Protected PDF, Linearized PDF / PDF/A | | |
| Optional Features | | ConnectKey® for DocuShare®, Xerox® Scan to PC Desktop® SE and Professional, other solutions available through various Xerox Business Innovation Partners | | |
| Fax | | | | |
| Standard Features | | N/A | Embedded Fax ⁴ , LAN Fax, Internet Fax, Server Fax | |
| Security | | | | |
| Standard Features | | McAfee® Embedded, McAfee ePolicy (ePO) Compatible, HDD Overwrite, 256-bit Encryption (FIPS 140-2 compliant), Common Criteria Certification (ISO 15408) ⁵ , Secure Print, Secure Fax, Secure Scan, Secure Email, Cisco® TrustSec Identity Services Engine (ISE) Integration, Network Authentication, SSL, SNMPv3, Audit Log, Access Controls, User Permissions | | |
| Optional Features | | McAfee Integrity Control, Smart Card Enablement Kit (CAC/PIV/.NET), Xerox® PrintSafe Software | | |
| Accounting | | | | |
| Standard Features | | Xerox® Standard Accounting (Copy, Print, Scan, Fax, Email), Network Accounting Enablement | | |
| Optional Features | | Equitrac Express®, Equitrac Office®, YSoft® SafeQ®, other network accounting solutions available through various Xerox Business Innovation Partners | | |

Xerox® ColorQube® 8700

| Device Specifications | | | | |
|-------------------------------------|---|-------------------|-------------------|------------------|
| Control Panel Languages | U.S. English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian | | | |
| Accessories | | | | |
| Optional | 525-sheet Tray 1,800-sheet High Capacity Feeder (HCF) Stand with Storage Drawer 650-sheet Finisher Smart Card Enablement Kit Xerox® USB Wireless Adapter McAfee Integrity Control Enablement Kit Foreign Device Interface (FDI) | | | |
| Electrical Requirements | | | | |
| North America | Voltage : 110-127 VAC Frequency: 50 / 60 Hz | | | |
| Europe | Voltage : 220-240 VAC Frequency: 50 / 60Hz | | | |
| Power Consumption | | | | |
| Printing (Max) | 110V: 1,050 watts; 220V: 1,213 watts | | | |
| Printing (Average) | 110V: 305 watts; 220V: 297 watts | | | |
| Standby Mode | 110V: 121 watts; 220V: 131 watts | | | |
| Power Save Mode | 110V: 58 watts; 220V: 56 watts | | | |
| Warm-up (from Power Save) | 2 minutes or less | | | |
| Cold Warm-up (from Power On) | 12 minutes or less | | | |
| Operating Environment | | | | |
| Required Temperature Range | 50° to 90° F (10° to 32° C) | | | |
| Required Relative Humidity | 10% to 80% | | | |
| Dimensions and Weight | Width | Depth | Height | Weight |
| 8700S and 8700X | 23.8 in. / 605 mm | 23.4 in. / 594 mm | 24.2 in. / 615 mm | 102 lbs. / 46 kg |
| 8700XF | 46.9 in. / 1,191 mm | 23.4 in. / 594 mm | 48 in. / 1,219 mm | 191 lbs. / 87 kg |
| 525-sheet Tray | 22.3 in. / 567 mm | 17 in. / 432 mm | 5 in. / 127 mm | |
| HCF | 28.3 in. / 718 mm | 25 in. / 635 mm | 14.5 in. / 368 mm | |
| Certifications | | | | |
| | FCC Part 15, Class A FCC Part 68 CE Mark applicable to Directives 2006/95/EC, 2004/108/EC and 1999/5/EC UL 60950-1/CSA 60950-1-07, 2nd Edition GOST Common Criteria (ISO 15408) Certification ⁵ Citrix IPv6 Ready Bonjour® Cerner MEDITECH SAP To view the latest list of certifications, go to www.xerox.com/OfficeCertifications . | | | |
| Paper Handling | | | | |
| Duplex Automatic Document Feeder | | | | |
| Capacity⁶ | 50 sheets | | | |
| Custom Sizes | 5.8 x 8.3 in. to 8.5 x 14 in. / 148 x 210 mm to 216 x 356 mm | | | |
| Weights | 16 lb. bond to 45 lb. cover / 60 to 120 gsm | | | |
| Multipurpose Tray 1 | | | | |
| Capacity⁶ | 100 sheets | | | |
| Custom Sizes | 3 x 5 in. to 8.5 x 14 in. / 76 x 127 mm to 216 x 356 mm | | | |
| Weights | 16 lb. bond to 80 lb. cover / 60 to 220 gsm | | | |

Xerox® ColorQube® 8700

| | |
|--|---|
| Media Types | Lightweight Plain paper Lightweight card stock Card stock Punched Letterhead Recycled Pre-printed Transparencies Labels Envelopes |
| Tray 2 | |
| Capacity⁶ | 525 sheets |
| Sizes | 5.8 x 8.3 in. to 8.5 x 14 in. / 148 x 210 mm to 216 x 356 mm |
| Weights | 16 lb. bond to 80 lb. cover / 60 to 220 gsm |
| Media Types | Lightweight Plain paper Lightweight card stock Card stock Punched Letterhead Recycled Pre-printed Labels Envelopes |
| Up to 3 Additional Trays or up to 2 Additional Trays with Optional High Capacity Feeder (Optional with 8700S and 8700X) | |
| Capacity⁶ | 525 sheets each |
| Sizes | 5.8 x 8.3 in. to 8.5 x 14 in. / 148 x 210 mm to 216 x 356 mm |
| Weights | 16 lb. bond to 80 lb. cover / 60 to 220 gsm |
| Media Types | Lightweight Plain paper Lightweight card stock Card stock Punched Letterhead Recycled Pre-printed Labels Envelopes |
| High Capacity Feeder (Optional with 8700S and 8700X; Standard with 8700XF) | |
| Capacity⁶ | 1,800 sheets |
| Sizes | 8.5 x 11 in., 8.5 x 14 in., A4 |
| Weights | 16 lb. bond to 32 lb. bond / 60 to 122 gsm |
| Media Types | Lightweight Plain paper Punched Letterhead Recycled Pre-printed |
| Total Capacity | |
| Standard Capacity⁶ | 8700S: 625 sheets 8700X: 625 sheets 8700XF: 3,475 sheets |
| Device Total Capacity⁶ | 8700S: 3,475 sheets 8700X: 3,475 sheets 8700XF: 3,475 sheets |
| Paper Output / Finishing | |
| Paper Output | |
| Standard Output Capacity⁶ | 8700S: 350 sheets 8700X: 350 sheets 8700XF: 950 sheets |
| Maximum Output Capacity⁶ | 8700S: 950 sheets 8700X: 950 sheets 8700XF: 950 sheets |

Xerox® ColorQube® 8700

| Finishing | | |
|--|--|----------------------------------|
| Convenience Stapler (Standard) | Up to 20 sheets ⁶ | |
| 650-sheet Finisher (Optional) | Stapling up to 50 sheets ⁶ <ul style="list-style-type: none"> • Stapling Sizes <ul style="list-style-type: none"> – Letter / 8.5 x 11 in. (216 x 279 mm) – Legal / 8.5 x 14 in. (216 x 365 mm) – 8.27 x 11.69 in. (A4) – Executive / 7.25 x 10.5 in. (184 x 267 mm) – B5 JIS / 7.17 x 10.12 in. (182 x 257 mm) • Stapling Weights <ul style="list-style-type: none"> – 16 lb. bond to 80 lb. cover (60 to 220 gsm) | |
| | Offset stacking | |
| Copy | | |
| First-copy-out Time (Letter/A4-size, from Platen to Center Tray) | As fast as 16 seconds color and black-and-white | |
| Sides (input:output) | 1-1, 1-2, 2-2, 2-1 | |
| Quantity | 1 to 9,999 | |
| Resolution (max.) | Up to 600 x 600 dpi | |
| Reduction / Enlargement | Variable zoom from 25% to 400% in 1% increments | |
| Concurrency | Program-ahead to allow job to be initiated while initial job is processed (Copy, Print, Fax and Scan) | |
| Copy Features | Annotation and Bates™ stamping (with color capability and font size adjustment) Authentication for Services (i.e. Color Copy) Auto Paper Select Auto Reduction & Enlargement to fit selected paper size Auto Tray Switching Automatic 2-sided/Duplex Booklet Creation Build Job Collation Covers Dividers (blank) Edge Erase ID Card Copy Image Quality Adjustments Image Shift (with Auto Center option) Invert Image (negative or mirror image) Large Job Interrupt Multi-up (up to 15 columns by 15 rows) Sample Set Save Job Settings Single Color Stapling Transparencies | |
| Print | | |
| Print Resolution | Print Driver / Print Mode | Resolution |
| | Adobe® PostScript® 3™ Fast Mode | 188 x 400 dpi |
| | Adobe PostScript 3 Standard Mode | 300 x 450 dpi |
| | Adobe PostScript 3 Enhanced Mode | 525 x 450 dpi (default) |
| | Adobe PostScript 3 High Resolution Mode | 525 x 2400 dpi (2400 FinePoint®) |
| | PCL Enhanced | 600 x 600 dpi |
| | PCL Standard | 600 x 400 dpi |

Xerox® ColorQube® 8700

| | |
|---|--|
| Print Features | <p>Application Defaults Banner Sheet Enable / Disable Bi-directional Status Custom Color Options (Color By Words) Cover Selection Delay Print (specific time) User Permissions Image Options (Toner Saver, Resolution (Standard, Enhanced, High) Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) Layout / Watermark (N-up (up to 16 pages per sheet), Multi-up, Booklet layout / finishing, Fit to new paper size) Overlays Paper Selection by Attribute LAN Fax (requires optional Fax Kit) Sample Set Saved Job (color jobs can be printed as monochrome) Secure Print with Timed Deletion Special Pages (exception page programming: covers, inserts, exception pages) Store and Recall Driver Settings Sustainability Features (Xerox® Earth Smart Settings, Duplex, N-up, Turn-off Banner and Print ID, Smart Sample Set, Hold All Jobs)</p> |
| Print from USB | <p>Allows walk-up printing from Type A USB port on front panel Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, PS, XPS, PCL Color jobs can be printed as monochrome</p> |
| Operating Systems | <p>Microsoft® Windows® XP SP3 (32- and 64-bit) Windows Server 2003 (32- and 64-bit) Windows Server 2008 and R2 (32- and 64-bit) Windows Server 2012 and R2 Windows Vista SP2 (32- and 64-bit) Windows 7 (32- and 64-bit) Windows 8 (32- and 64-bit) Windows 8.1 (32- and 64-bit) Mac OS 10.7, 10.8, 10.9 Linux® Redhat® Fedora® Core 19 x86 Ubuntu® 13.10 x64 openSUSE® 13.1 x64</p> |
| Network Protocols | <p>TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6,WSD NetWare: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway) AppleTalk®: EtherTalk® Microsoft Windows Networking over IP Apple Bonjour® IPv6 Secure FTP Most protocols not in use can be disabled</p> |
| Administrative Protocols | <p>DHCP, BOOTP, SNMP, WINS, SLP® v2, HTTP, HTTPS, DHCP Autonet, SSL, NTP, DNS, SSDP</p> |
| Fonts | <p>PCL: 93 scalable fonts, line printer and bitmap font (including Cyrillic font support) PostScript 3: 173 Type 1 fonts, 2 Multiple Master fonts</p> |
| Xerox® Mobile Express Driver® | <p>Makes it easy for mobile users to find, use and manage Xerox® and non-Xerox devices in every new location. Plug into a new network, and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of “favorite” printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.</p> |
| Xerox® Global Print Driver® | <p>A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.</p> |
| Xerox® Pull Print Driver | <p>Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.</p> |
| Print Solutions | |
| Xerox® Mobile Print Cloud (Optional) | <p>Xerox® Mobile Print Cloud addresses the needs of businesses with a mobile workforce and puts you ahead of the evolving mobile print need, but without burdening staff, budget or infrastructure. Getting started takes only a few minutes via the cloud. Print from any mobile device to nearly any brand of printer, Accurate printing with true Microsoft® Office® rendering and more. Print what you need, when, where and how you need it.</p> |
| Xerox® Mobile Print Solution (Optional) | <p>Xerox® Mobile Print Solution is an ideal choice for sites that have additional requirements for control and security with an onsite server. Xerox® Mobile Print Solution allows users to print from most mobile devices to nearly any brand of printer or MFP without drivers or added complexity. Simply enter a release code (PIN) at the device and get accurate printing with true Microsoft Office rendering and more to use with your server for private, onsite deployment.</p> |
| Unified Address Book for Fax, Internet Fax, Email and Scan to... | |
| Features | <p>Services supported: Fax, Internet Fax, Email, Scan to Maximum contacts: 5,000 Contacts: Supports 1 or more destinations Favorites for quick access of fax numbers, emails, etc.</p> |

| Scan | |
|---|--|
| Concurrency | Scan while the system is printing, copying, or while it is transferring scan to network or fax jobs (priority is for return of scanned originals and printing concurrent jobs) |
| Input Speed | Black-and-white: Scan up to 40 ipm – 8.5 x 11 in. / A4 (210 x 297 mm) Color: Scan up to 40 ipm – 8.5 x 11 in. / A4 (210 x 297 mm) |
| Resolution | 72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black-and-white), 8-bit (grayscale), 24-bit (color) |
| Maximum Scan Area | Platen: Up to 8.27 x 11.69 in. / A4 DADF: 8.5 x 14 in. / 216 x 356 mm |
| Scan Template Management | Support 250 scan templates Create Xerox® CentreWare® IS scan templates and share via device cloning to other MFPs Confirmation sheet options |
| Network Protocols | sFTP, FTP, SMB, NetWare, HTTP, HTTPS |
| File Compression | Color TIFF (TIFF 6.0 or TTN2 with JPEG, LZW) Black-and-white TIFF (G3MH, G4 MMR compression - single or multiple pages) Searchable PDF and PDF/A (MRC, JPEG, G3 MH, G4 MMR, JBIG 2 Huffman, JBIG Arithmetic Compression, Deflate (for Black-and-white and within MRC)) Linearized PDF / PDF/A |
| Document Management Fields (Meta Data) | Features only available in Network Scan to File Templates: <ul style="list-style-type: none"> • 1 to 6 user programmable metadata fields per network scan to file templates and unlimited fields within the template – Metadata field consists of field name, default value and other configurations • Customized fields viewed on user interface for variable data input |
| Scan Features | Mixed Size Originals Scan Build Job Compression Quality/File Size Control Original Type (Photo and Text, Photo, Text, Map, Newspaper / Magazine) Auto Background and Shadow Suppression Size for Size (for mixed size originals) TWAIN Support / WIA Support Bound Originals Edge Erase Reduction/Enlargement Single Touch Scan buttons (up to 10) |
| Scan to Email (Standard) | |
| Scan Features | <ul style="list-style-type: none"> • Email signatures (6 lines each of 128 character max), email message body (user configurable), email CentreWare IS confirmation sheet options • Scan to Email S/MIME Encryption • Email signing (requires Smart Card option) • Auto send to self |
| Directory Access | Address list via LDAP (Windows Archive Directory, Exchange, Notes, Domino) Downloaded address list (comma-separated file format) Utilizes the Unified Address Book |
| Scan to... (Standard) | |
| Features | Scan to USB Scan to Network Folder (uses Unified Address Book entries) |
| Network Scanning – Software Solutions | |
| Xerox® Scan to PC Desktop® Professional (Optional) | A desktop offering that provides advanced document imaging, archiving, editing and organization tools: <ul style="list-style-type: none"> • Nuance PaperPort Professional image viewing and file management software <ul style="list-style-type: none"> – Complete PDF functionality – Secure PDF workflow of all scanning applications • Nuance OmniPage Pro Office (for desktop/client installation) – Professional OCR software for digital archiving and document conversion • Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox® ColorQube to individual desktops. Also includes email inbox polling capability |
| Xerox® ConnectKey® for DocuShare® (Optional) | Xerox® ConnectKey for DocuShare, a one-step scan-to-workflow solution, simplifies the process of incorporating hard copy content into enterprise document flows. Users can easily scan documents directly into a DocuShare collection or Windows folder via a multifunction printer (MFP). |

| Security | |
|---|---|
| Features | <ul style="list-style-type: none"> • Expanded Authentication <ul style="list-style-type: none"> – Network authentication to access device and/or device services via- Kerberos (UNIX / Windows Server 2003 / Windows Server 2008), SMB (Windows Server 2003 / Windows Server 2008), NDS, LDAP – Local Authentication (internal database) – Smart Card authentication -144k CAC / PIV Card Support (2048 bit certificate key) /.NET • Secure Data <ul style="list-style-type: none"> – Digitally signed PDF (when using Smart Card authentication) – Encrypted Scan to Email – Encrypted Password Protected PDF (when using Email and Network Scan Templates only) – Secure Print (up to 10 digit PIN or Network Authentication) – Immediate Image Overwrite – On Demand Image Overwrite (Scheduled, Manual), includes sanitation of unused area of disk – FIPS 140-2 256 bit Hard Disk Encryption • Expanded Authorization <ul style="list-style-type: none"> – SA access based on network credentials – Authorization per user per service – User Permissions required to access Print and Print Features (e.g. color access, or time restrictions) reflects in the print driver • Secure Network Access • IP Filter, IPsec, IPv6, SSL v3.0, SNMPv3, HTTPs, 802.1X, Cisco® TrustSec Identity Services Engine (ISE) integration, Device Security – McAfee® Embedded Security, Port disablement including USB ports, Audit Log, Hide Print Job Names, McAfee Integrity Control (optional) • Common Criteria Certification ISO 15408⁵ |
| Fax | |
| Embedded Fax⁴, LAN Fax, Internet Fax, Server Fax (Not available with 8700S; Standard with 8700X and 8700XF) | |
| Fax Speed | Up to 33.6 Kbps (analog) |
| Memory | Uses device memory |
| Resolution | Up to 600 x 600 dpi (Super Fine) resolution Up to 200 x 200 dpi (Fine) resolution Up to 200 x 100 dpi (Standard) resolution |
| Compression | MH, MR, MMR, JBIG |
| Fax Features | Duplex Scanning Reports Auto Redial Auto Reduction Cover Page Delayed Send Fax Forward to Email Memory Receive Mixed-size Originals Phone Book Search Junk Fax Prevention Polling Secure Fax Speed Dials (up to 200 individual, 100 group) |
| Device Management | |
| Management Support | SNMP Version 1, SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP MIB access (IETF-MIBII RFC 1213), Host Resources MIB RFC 2790, Printer MIB RFC 1759 v.2 |
| Xerox® CentreWare® Web | A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows, UNIX or any other operating system: <ul style="list-style-type: none"> • Works with any SNMP-managed printer from any manufacturer. • Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management. • Requires Windows XP, Vista or Windows 7 and Internet Explorer 6.0 and higher. • CentreWare Integration available for Tivoli® NetView®, Unicenter TNG®, Microsoft Management Console (MMC), HP® OpenView® |
| Novell NDPS/NEPS | Server gateway application: centralized management tool. |
| Xerox® Device Manager | Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides: <ul style="list-style-type: none"> • Device monitoring and troubleshooting • Extensive reporting and discovery of new devices • Usage collection, chargeback and billing capabilities |
| Xerox® Device Types for SAP Environment | Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Program, provides seamless connectivity between SAP systems and your Xerox® printers and MFPs. And as an SAP customer you benefit from having SAP-certified Xerox® device types available right from SAP's online delivery model. SAP-certified device types for Xerox® printers and MFPs are available to download. www.office.xerox.com/software-solutions |

Xerox® ColorQube® 8700

| | |
|---|--|
| Xerox® Device Types for SAP R/3 Intelligent Barcode Utility (optional) | Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAP environment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Center Barcode Fonts. Information available at www.office.xerox.com/software-solutions |
| Xerox® Barcode Pro PS (optional) | Enables intelligent PostScript printing on Xerox® multifunction systems by storing Xerox® software, as well as, the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP client or mainframe) that supports PostScript printing. Information available at www.office.xerox.com/software-solutions |
| CentreWare Internet Services – Integrated Web Pages Provided by the Device | |
| Device Status | Web server embedded in Network Controller: <ul style="list-style-type: none"> • Tray status/contents • Consumables status • Alerts Remote Control Panel |
| Job Submission | Print ready files: PS, PCL, TIFF, PDF, JPG, XPS4, TXT, PRN Output feature selection (2-sided, output color, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint) |
| Device Administration | Allows simple, remote installation setting of configuration options and management of the device |
| Browsers | Internet Explorer 7.x, 8.x, 9.x Safari 5.x Mozilla Firefox 4.x, 5.x, 6.x, 7.x, 8.x, 9.x, 10.x, 11.x Opera 11.x Chrome 12 |
| Support | Install print / scan drivers and online support available via web page |
| Languages Supported | International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish or Russian, Simplified Chinese, Korean, Japanese |
| Remote Services | |
| Xerox® MeterAssistant® | Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time. |
| Xerox® SuppliesAssistant® | Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory. |
| MaintenanceAssistant | Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting/repair process. Diagnostic data is sent to Xerox, allowing for problems to be solved faster with increased uptime. |
| Accounting | |
| Xerox® Standard Accounting (Standard) | |
| Tracking | Copy, Print, Fax, Scan and Email usage |
| Accounting | Up to 2,497 User accounts (User ID) Up to 500 General accounts (Client) Up to 498 Group accounts (Department) |
| Features | <ul style="list-style-type: none"> • Administrator can manage the feature via the Web User Interface or device control panel in tools • Administrator has the ability to import or export user accounts, Group Accounts, General Accounts and User limits via an industry standard CSV file |
| Accounting Options – Network Accounting – Third Party Enablement | |
| | <ul style="list-style-type: none"> • Enhanced network accounting with up to the minute data on how the system is being used • Comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and server fax • Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.com • Security enhancements with the addition of HTTPS protocol support • Device requests account authentication from third party server enabling larger databases of users and accounts • Accept Authentication Login at control panel and pass to third party Networking Account • Interface with third party accounting terminal for accounting user interface |
| What Comes in the Box | |
| | ColorQube 8700 One of each (Cyan, Magenta, Yellow: 2,100 print capacity ⁷ ; Black: 2,250 print capacity ⁷) Xerox® Genuine Solid Ink sticks Quick Use Guide Documentation CD (with User Manual, Quick Install Guide, Print Drivers and Warranty Statement) Staple Cartridge (installed) Fax Cord and Power Cord |

Xerox® ColorQube® 8700

| Supplies and Options | Description | Order Number |
|----------------------------------|--|--------------|
| Genuine Xerox® Solid Ink | 2 Sticks Cyan: 4,200 pages ⁷ | 108R00990 |
| | 2 Sticks Magenta: 4,200 pages ⁷ | 108R00991 |
| | 2 Sticks Yellow: 4,200 pages ⁷ | 108R00992 |
| | 2 Sticks Black: 4,500 pages ⁷ | 108R00993 |
| | 4 Sticks Black: 9,000 pages ⁷ | 108R00994 |
| Staple Cartridges | Convenience Stapler refill cartridge | 108R00823 |
| | Finisher Stapler refill cartridge | 008R12964 |
| Routine Maintenance Items | Cleaning Unit (Standard capacity): 10,000 pages ⁷ | 109R00784 |
| | Cleaning Unit (Extended capacity): 30,000 pages ⁷ | 109R00783 |
| Accessories | 525-sheet Tray | 097S04383 |
| | 1,800-sheet High-Capacity Feeder | 097S04382 |
| | Stand with Storage Drawer | 097S04388 |
| | 650-sheet Finisher | 097S04324 |
| | Foreign Device Interface | 097S04408 |
| | Smart Card Enablement Kit | 498K17546 |
| | Xerox® USB Wireless Adapter | 497K11500 |

¹ Standard and Fast Color speeds are available for printing in PostScript only. Copy settings are limited to High Resolution/Photo and Enhanced Mode speeds.

² Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

³ Expected regular monthly throughput.

⁴ Analog phone line required.

⁵ Code Base 071.160.202.26500

⁶ Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.

⁷ Average standard pages. Declared Yield in accordance with ISO/IEC 24711. Yield will vary based on image, area coverage and print mode.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling program. For more information, visit www.xerox.com/about-xerox/recycling.

For more information, visit us at www.xerox.com/office

