

WorkCentre® 3550

Black-and-White Multifunction Printer



WorkCentre 3550

A value-driven performer that offers printing, copying, faxing and scanning.

WorkCentre 3550	
Output Speed	
Single-Sided	Up to 35 ppm 8.5 x 11 in. Up to 33 ppm A4 (210 x 297 mm)
Automatic Two-Sided	Up to 17 ppm 8.5 x 11 in. Up to 16 ppm A4 (210 x 297 mm)
Paper Handling - Input	
Duplex Automatic Document Feeder	
Capacity¹	60 sheets
Sizes	Custom Sizes: 2.75 x 5.7 in. to 8.5 x 14 in. to 8.5 x 14 in / 69.9 x 145 mm to 216 x 356 mm
Weights	12 lb. bond to 28 lb. bond (50 to 120 gsm)
Multipurpose Tray	
Capacity¹	50 sheets
Sizes	Custom Sizes: 3 x 5 in. to 8.5 x 14 in. (76 x 127 mm to 216 x 356 mm)
Weights	16 lb. bond to 43 lb. bond (60 to 163 gsm)
Media Types	Plain paper Letterhead Bond Heavyweight Lightweight Recycled Archive Labels Drilled Postcard Transparencies Envelopes Custom 1-7

¹ Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.

Main Tray	
Capacity¹	500 sheets
Sizes	Custom Sizes: 5.8 x 8.3 in. to 8.5 x 14 in. / 148 x 210 mm to 216 x 356 mm
Weights	16 lb. bond to 28 lb. bond (60 to 105 gsm)
Media Types	Plain paper Heavyweight Lightweight Recycled Archive Letterhead Drilled
Additional Tray (Optional)	
Capacity¹	500 sheets
Sizes	Custom Sizes: 5.8 x 8.3 in. to 8.5 x 14 in. / 148 x 210 mm to 216 x 356 mm
Weights	16 lb. bond to 28 lb. bond (60 to 105 gsm)
Media Types	Plain paper Heavyweight Lightweight Recycled Archive Letterhead Drilled
Paper Handling - Output	
Standard Output	250 sheets
Print	
First-Page-Out-Time	As fast as 8.5 seconds
Print Resolution	600 x 600 dpi (up to 1200 x 1200 enhanced image quality)
Memory (Std/max)	256 MB / 512 MB
Processor	360 MHz
Language Support	Postscript® 3™ compatibility PCL® 5e emulation PCL® 6 emulation
Connectivity	10/100 Base-TX Ethernet, USB 2.0
Printing Features	Automatic two-sided printing Custom page size Toner save mode Proof print Secure print Watermarks N-up Fit to page Overlay Reduce/Enlarge Poster Scaling Booklet printing Print from USB memory device

¹ Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.

Print Drivers	Windows® XP (32/64bit) / 2003 (32/64bit) / 2008 Server (32/64 bit) / Vista (32/64bit) / Windows 7 (32/64bit) / 2008 R2 (64bit) Macintosh® OS X v10.3-10.6 RedHat Enterprise Linux WS 4, 5 (32/64bit) Fedora Core 2-10 (32/64bit) SuSE Linux 9.1 (32bit) OpenSuSE 9.2, 9.3, 10.0, 10.1, 10.2 10.3, 11.0, 11.1 (32/64bit) Mandrake 10.0, 10.1 (32/64bit) Mandriva 2005, 2006, 2007, 2008 (32/64bit) Ubuntu 6.06, 6.10, 7.04, 7.10, 8.04, 8.10 (32/64bit) SuSE Linux Enterprise Desktop 9, 10 (32/64bit) Debian 3.1, 4.0, 5.0 (32/64bit) Xerox® Mobile Express Driver™ Xerox® Global Print Driver®
Font Capability	136 PostScript® fonts 111 PCL® fonts
Copy	
Document Scanner	Duplex Automatic Document Feeder with 60-sheet capacity
Sides (input:output)	1:1, 1:2, 2:2 and 2:1
Quantity	1 to 999
Resolution	600 x 600 dpi (up to 1200 x 1200 enhanced image quality)
Concurrency	Concurrent scanning and printing
First-Copy-Out-Time	As fast as 10 seconds
Copy Features	Automatic two-sided Reduce/Enlarge Background Suppression Collation (DADF only) ID Card Copy N-up (2-up/4-up) Book copy Booklet creation Clone copy (Platen only) Poster copy (Platen only)
Foreign Device Interface (Optional)	Interface to third-party access control devices, coin machines and card readers Supports a variety of vending stations available through the Xerox Custom Application Service
Fax	
Embedded Fax², PC Fax (1 line)	
Fax Speed	33.6 Kbps
Memory	Up to 7 MB
Resolution	Up to 600 x 600 dpi (superfine) resolution
Compression	MH, MR, MMR, JPEG and JBIG

² Analog phone line required

Fax Features	<p>Color fax send Two-sided Fax forward to Fax/Email and Server (FTP, SMB) PC Fax (send only) Secure fax receive Searchable address book Auto redial Last number redial Pause Distinctive ring External phone interface Journal Confirmation reports Auto dial list Junk fax barrier Persistent Flash Memory Up to 209 group dial locations Broadcast fax Delayed fax Memory receive Auto file size reduction</p>
Scan	
Capability	Black-and-white, grayscale and color scanning
Concurrency	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs
Input Speed	26 ipm (images per minute) black-and-white (8.5 x 11 / A4) 8 ipm color (8.5 x 11 / A4) @ 300 dpi
Resolution	300 x 300 dpi 200 x 200 dpi 100 x 100 dpi
Maximum Scan Area	8.5 x 14 in. / 216 x 356 mm
Network Protocol	FTP SMTP SMB
File Formats	JPG PDF TIFF Multipage TIFF
Supported Scan Destinations	Scan to Email (includes support for Global Address Book via LDAP and up to 200 local address book entries) Network Scan to PC Scan to FTP and SMB Direct Scan to Applications, including OCR (software included) Scan to USB memory device
Scanning Solutions	
Scan to PC Desktop® Personal Edition	<ul style="list-style-type: none"> • A desktop and server-based offering that provides document imaging, archiving, editing and organization tools • Nuance® PaperPort SE 11.0 – image viewing and file management software • OmniPage® 16 SE (for desktop/client installation) – OCR and file format conversion software • Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox WorkCentre to individual desktops

Security	
Security Features	802.1x Kerberos SNMPv3 HTTPS Secure Fax SSL IPv6 LDAP IP Filtering Scan to Email with authentication
Device Management	
Xerox CentreWare® Web	
	<ul style="list-style-type: none"> • A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system • Works with any SNMP-managed printer from any manufacturer • Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic Accounting and asset management
Xerox CentreWare® Internet Services - Integrated Device Web Page	
Device Status	Web server embedded <ul style="list-style-type: none"> • Tray status/contents • Consumables status
Print Queue Viewing	Job print queue management
Job Submission	Print-ready files (PS, PCL, TIFF, PDF) Output feature selection
Device Administration	Allows simple, remote installation setting of configuration options and management of the device
Browsers	Netscape® 6.2 Netscape® 7.x (Mozilla 1.x) Netscape® 8.x Microsoft® Internet Explorer 5.5.x, 6.x, 7.x Apple® Safari™ 1.2.x, 2.x Firefox® 1.5.x, 2.x
Device Specifications	
Duty Cycle	
	Up to 75,000 pages / month ³
Electrical Requirements	
	220-240 VAC, 50/60 Hz 110-127 VAC, 50/60 Hz ENERGY STAR® qualified
Power Consumption	
Printing	600 watts
Standby	<60 watts
Power save	<20 watts
Warm up (from sleep mode)	<15 seconds
Operating Temperature Range	50° to 90° F (10° to 32° C)

³ Print volume uniformly distributed over 30 days

WorkCentre® 3550

Relative Humidity Range	20 % to 80 %			
Sound Pressure Levels				
Printing	55 dB(A)			
Standby	39 dB(A)			
Dimensions and Weights	Width	Depth	Height	Weight
Product (without print cartridge)	22.9 in. / 582 mm	19.2 in. / 488 mm	21.8 in. / 553 mm	51.59 lbs / 23.4 kg
Package	26.6 in. / 676 mm	24.3 in. / 619 mm	27.4 in. / 696 mm	65.48 lbs / 29.7 kg
Certifications				
	Listed UL 60950 CE Mark applicable to Directives 2006/95/EC 2004/108/EC and 99/5/EC, FCC Part 15 Class A, FCC Part 68 ENERGY STAR® qualified			
What Comes in the Box				
	<ul style="list-style-type: none"> • WorkCentre 3550 Multifunction Printer • Print cartridge (5,000 print capacity) • World Kit CD (includes Printer Installer, utilities, Software and documentation) • Power cord • Fax cord 			
Supplies and Options	Description	Order Number		
	High-Capacity Print Cartridge – approximately 11,000 standard pages ⁴	106R01530		
	Standard-Capacity Print Cartridge – approximately 5,000 pages ⁴	106R01528		
	500-sheet Tray	098N02190		
	256 MB Memory Upgrade	098N02189		
	Stand	097N01674		
	Foreign Device Interface	097N01676		
	Wireless Network Adapter	097S03740		

⁴ Average standard pages. Declared Yield in accordance with ISO/IEC 19752. Yield will vary based on image, area coverage and media used.



For more information, call **1-877-362-6567** or visit us at **www.xerox.com/office**

