

# WorkCentre® 7346

## Color Multifunction Printer



**WorkCentre 7346**  
shown with High-Capacity  
Tandem Tray and Professional Finisher options.

WorkCentre® 7346	
<b>Output Speed – Printing and Copying</b>	
<b>Black and White</b>	Up to 45 ppm 8.5 x 11 in. (A4/210 x 297 mm), Up to 27 ppm 8.5 x 14 in. (216 x 356 mm), Up to 22 ppm 11 x 17 in. (A3/297 x 420 mm)
<b>Color</b>	Up to 40 ppm 8.5 x 11 in. (A4/210 x 297 mm), Up to 24 ppm 8.5 x 14 in. (216 x 356 mm), Up to 20 ppm 11 x 17 in. (A3/297 x 420 mm)
<b>Print Specifications</b>	
<b>System</b>	
<b>Memory</b>	1.5 GB
<b>System Disk</b>	Minimum 40 GB
<b>Network Printing – Network Controller</b>	
<b>Processor</b>	667 MHz
<b>Printer Languages</b> (auto sensing/ switching)	Adobe Postscript® 3 TIFF PCL5c PDF 1.5 PCL 6 HP-GL2™ XPS®
<b>Network Printing – Resolution</b>	
	Print Engine: 1200 x 1200 dpi

Network Printing – Printing features	
	Print Calibration Secure print Delay print (specific time) Sample set Booklet creation Cover selection Paper selection by attribute N-up Saddle-stitch booklet making (requires Professional Finisher) Hole Punch (requires Professional Finisher or Advanced Office Finisher) Booklet Fold / V Folding (requires Professional Finisher) Watermark Fit to new paper size Transparency Separators Banner sheet enable/disable Output tray selection Image quality: High Speed (600 x 600 x 1), High Quality (600 x 600 x 8), High Resolution (1200 x 1200 x 1) Draft mode Store and recall driver settings Reduce/enlarge Mirror image Margins Bi-Directional
Print Protocols and Networks	
<b>Physical</b>	Ethernet 100BaseT/10BaseT USB printer port (optional) Wireless Ethernet (IEEE 802.11b) via third-party adapters Parallel Port (optional)
<b>Operating Systems</b>	Microsoft® Windows® XP® 32-bit, XP 64-bit, Windows Server 2003 32-bit, Windows Server 2003 64-bit, Windows Vista 32-bit, Windows Vista 64-bit Mac OS® 10.3 and above AIX 5Iv5.3 HP UX 11.0, 11i v2 Solaris 8, 9, 10 Linux® FedoraCore 1, 5 RedHat Enterprise Linux 4 SUSE 10.x
<b>Network Protocols</b>	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6 Netware: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway) AppleTalk®: EtherTalk® Microsoft Windows Networking over IP and NetBEUI (All protocols not in use can be disabled)
<b>Administrative Protocols</b>	DHCP, BOOTP, SNMP, WINS, DDNS, SLP® v2, HTTP, RARP, DHCP Autonet, SSL
<b>Fonts</b>	Postscript 3: 136 Type 1 fonts, 2 Multiple Master fonts PCL: 84 scalable fonts, line printer bitmap font

# WorkCentre 7346

Print Drivers	Environment	PCL5c and PCL 6	PostScript
(Vista XPS mini driver available)	Windows 2003/XP 32 Bit Windows 2003/XP 64 Bit Windows Vista/Vista 32 Bit Windows Vista/Vista 64 Bit (Microsoft certified)	Bidirectional with user-selectable interface (standard and enhanced)	Bidirectional with user-selectable interface (standard and enhanced)
	Macintosh® System OS 10.3.0 and above	N/A	Enhanced PPD file
	UNIX	N/A	Bidirectional with Xerox Custom Graphical User Interface
<b>Print Submission Tools</b>	<ul style="list-style-type: none"> <li>• Command prompt LPR/UNIX tool for print submission</li> <li>• Submission Tool with full feature set (includes administration, GUI/TTY print driver and software installation)</li> <li>• Contents Bridge tool supports TIFF/PDF/XPS and Office 2007 direct print</li> </ul>		
<b>Device Management</b>			
<b>Management Support</b>	SNMP Version 1, SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP MIB access (IETF-MIB II RFC 1213), Host Resources MIB RFC 2790, Printer MIB RFC 1759 v. 2		
<b>Xerox CentreWare Web</b>	<ul style="list-style-type: none"> <li>• A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system</li> <li>• Works with any SNMP-managed printer from any manufacturer</li> <li>• Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management</li> </ul>		
<b>IP Filter</b>	Allows administrator to control print access to device via IP address.		
<b>Xerox CentreWare® for Unicenter TNG®</b>	<ul style="list-style-type: none"> <li>• Provides added identification to the general discovery performed by Unicenter TNG and the ability to see the device under a Unicenter TNG Business Process View</li> <li>• Provides full integration with event management and the choice to integrate with problem management and advanced Help Desk</li> </ul>		
<b>Xerox CentreWare® for Tivoli® Netware®</b>	<ul style="list-style-type: none"> <li>• Provides for the identification of Xerox N-Series printers and WorkCentre multifunction systems in the general discovery performed by Tivoli NetView</li> <li>• Provides the ability to see the discovered Xerox printers/devices in a Xerox Printers Set in addition to the Printers SmartSet</li> <li>• Provides full integration with the NetView and Event Browser and Tivoli Enterprise Console (TEC)</li> </ul>		
<b>Xerox CentreWare® for Microsoft Management Console (MMC)</b>	CentreWare MC Snap-in supports printer discovery and management via a Microsoft Management Console (MMC) link to an embedded Web server. It is a general-purpose management display framework for hosting administrative tools.		
<b>Xerox CentreWare® for HP® OpenView®</b>	<ul style="list-style-type: none"> <li>• Provides for the identification of Xerox N-Series printers and WorkCentre multifunction devices in the general discovery performed by HP OpenView</li> <li>• Provides the ability to see the current status of discovered Xerox printers/devices under a Xerox PrinterMap and IP Map via color-coded icons</li> <li>• Provides traps and message updates to the OpenView alarm browser and the ability to launch CentreWare Internet Services for device management directly from OpenView</li> </ul>		
<b>Xerox Device Types for SAP R/3 Environment</b>	<p>Simplifies printing in SAP R/3 environments by providing users of SAP R/3 v4.6C, 4.x and 3.x ERP applications with enhanced WorkCentre printing functionality (PostScript and PCL):</p> <ul style="list-style-type: none"> <li>• Simplex or duplex printing</li> <li>• Finishing – single or dual stapling</li> <li>• Tray pull location from any tray</li> <li>• Print security via PIN ID capability at the WorkCentre</li> </ul>		

<b>Xerox SAP R/3 Intelligent Barcode Utility (Optional)</b> <i>Purchase via Type House 800-445-3668</i>	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer on the SAP R/3 4.x (or higher) network. Used in conjunction with Xerox Device Types for SAP R/3 Environment and Xerox Font Center Barcode Fonts. Utility automatically calculates checksum, placement of start/stop characters, and encoding of data string Web server embedded on network controller <ul style="list-style-type: none"> <li>• Tray status/contents</li> <li>• Consumables status</li> </ul>
<b>Xerox Barcode Pro PS (optional)</b> <i>Purchase via Type House 800-445-3668</i>	Enables intelligent PostScript printing on Xerox multifunction printers by storing Xerox software as well as the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (client or mainframe) that supports PostScript printing. Automatically calculates the check digit, places start/stop and middle bar characters in the data string, compresses and encodes the data string, and rotates the barcode through 90 or 270 degrees.
<b>Smart eSolutions</b>	
<b>Meter Assistant</b>	Device Direct or via proxy
<b>Supplies Assistant</b>	Device Direct or via proxy
<b>Centware® internet services – Integrated device Web Page</b>	
<b>Device Status</b>	Web server embedded on network controller <ul style="list-style-type: none"> <li>• Tray status/contents</li> <li>• Consumables status</li> </ul>
<b>Print Queue Viewing</b>	Complete job print queue management – hold, release, promote and delete
<b>Job Submission</b>	Print-ready files (PS, PCL, TIFF, PDF, XPS) Output feature selection
<b>Device Administration</b>	Allows simple, remote installation setting of configuration options and management of the device
<b>Browsers</b>	Windows XP: Netscape Navigator®, Firefox® Microsoft Internet Explorer Macintosh 9.x/OS X: Netscape Navigator 6.x, Mac Safari, Firefox Linux: Netscape® 6.x
<b>EFI Fiery System 8e® Network Controller (Optional)</b>	
<b>Processor</b>	2.8 GHz
<b>Memory (ESS)</b>	512 MB
<b>System Disk</b>	80 GB minimum
<b>Print Languages (PDL)</b>	PostScript 3 PCL 6 emulation
<b>Features</b>	Command WorkStation capability via a PC or MAC (customer to provide) with Queue Management, Job Preview, Merge and Properties and Manual Load Balancing Pantone Calibrated Certification Expert Color Settings; Profile, Rendering and Simulation Variable Data – Free Form
<b>Optional</b>	Hot folders Optional Virtual Printer Spot On Color Management Auto Trapping Impose

Scan Specifications	
<b>Scanning (Optional)</b>	
<b>Capability</b>	Color Scanning, Greyscale, Black and White, Auto Color
<b>Concurrency</b>	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs
<b>Input Speed</b>	Scan at 50 ipm monochrome/45 ipm color (216 x 279 mm/A4 long edge feed)
<b>Resolution</b>	600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi Bit depth: 1 bit (monochrome), 8 bit (greyscale), 24 bit (color)
<b>Maximum Scan Area</b>	11.7 x 17 in. /297 x 432 mm
<b>Secure Access and Authentication</b>	Optional secure device login with network user name and password Supports: Kerberos (Windows 2000/UNIX/Windows Server 2003), SMB (Windows 2000/Windows Server 2003/Vista) LDAP
<b>Network Protocol</b>	FTP via TCP/IP Microsoft SMB via TCP/IP NetWare, HTTP and HTTPS
<b>File Formats</b>	TIFF 6.0 or TTN2 with JPEG, G3MH, G4 MMR compression (single page or multiple pages) PDF with MRC, JPEG, G3 MH, G4 MMR, MRC, JPEG or JBIG2 compression JPEG XPS Text Searchable PDF Encrypted PDF
<b>Document Management Fields</b>	One to six user-programmable metadata fields per scan job Customized fields viewed on user interface Variable data entered using virtual keyboard
<b>Scan Feature Options</b>	Mixed size originals Bound originals Edge erase Reduction enlargement Fit to size Scan Build Job Compression Quality/File Size Control Original type (photo and text, photo, text) Auto Background and Shadow Suppression
<b>Supported Scan Destinations (Varies by scanning software options purchased.)</b>	Scan to network server Scan to remote email destinations via direct SMTP addresses or via various network scanning software options Scan to application (Electronic Document Management System/Repositories) Scan to Microsoft Exchange 2000 Web Folders Scan to PC Desktop™ (Professional and SE editions) Scan to Windows XP client SMB or FTP Scan to Mailbox Scan to Home
<b>Scan to PC Desktop SE</b>	<ul style="list-style-type: none"> <li>• A desktop and server-based offering that provides document imaging, archiving, editing and organization tools</li> <li>• ScanSoft PaperPort (for desktop/client installation) – image viewing and file management software</li> <li>• ScanSoft OmniPage (for desktop/client installation) – OCR and file format conversion software</li> <li>• Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox WorkCentre to individual desktops.</li> </ul>

<b>Scan to PC Desktop Professional</b>	<ul style="list-style-type: none"> <li>• A desktop and server based offering that provides document imaging, archiving, editing and organization tools</li> <li>• ScanSoft PaperPort Pro (for desktop/client installation) – image viewing and file management software</li> <li>• ScanSoft OmniPage Pro (for desktop/client installation) – OCR and file format conversion software</li> <li>• Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox WorkCentre to individual desktops. Also includes an Email inbox polling capability.</li> </ul>
<b>Email (Included with Scanning Option)</b>	
<b>Capability</b>	Color scanning, Auto Color, Greyscale, Black and White Direct document email from device Manual or directory Exchange/Notes/LDAP address searching
<b>Network Protocol</b>	SMTP, S/MIME, LDAP, LDAPs encoded
<b>Authentication</b>	Device login with network user name and password Supports: Kerberos (UNIX/Windows 2003 Server), SMB, (Windows 2000/Windows 2003 Server) LDAP Domino
<b>Directory Access</b>	Corporate address list via LDAPv3 Downloaded address list (comma-separated file format)
<b>Scan to Mailbox (Included with the Scanning Option)</b>	
<b>Capability</b>	Color, Auto Color, Black and White
<b>Features</b>	Images can be scanned, printed and faxed directly to the device hard drive and stored in a mailbox. Scan and fax images that are stored in the mailbox can then be emailed, sent via fax, sent via IFax, routed to a PC, an FTP or SMB site via Job Flow Sheets.
<b>Thumbnail Preview (Optional)</b>	
	Images that are stored in the mailbox can be viewed at the device.
<b>Fax Specifications</b>	
<b>Network Fax Server Integration (Optional)</b>	
<b>Fax Send Features</b>	One- or two-sided scanning Phone number entry Add to send list (50 numbers maximum) Delay send (specific time) Resolution selection (super fine/600 x 600, super fine/400 x 400, fine/200 x 200, standard/200 x 100 dpi) Original type (photo and text, photo, text)
<b>Fax Print Features</b>	One- or two-sided printing Quantity Staple on/off Collate on/off Finisher output tray selection (top tray or main tray) Secure print on/off
<b>Fax Vendors</b>	Multiple vendors, certified by the Xerox Business Partners Program For details, visit <a href="http://www.xerox.com">www.xerox.com</a>
<b>Fax (Optional) – Standard with One or Three line Fax option</b>	
	ITY (CCITT) group 3 quality/resolution superfine/600x600, superfine/400 x 400, fine/200x200, standard/200x100 dpi
<b>Speed/Modem(s)</b>	V.34 modem(s): 33,600 bps. Less than four seconds per page transmission time. ISDN via third-party adapter.
<b>Speed/Compression</b>	MH/G3, MMR/G4, JBig Super G3

# WorkCentre 7346

<b>Fax Send Features</b>	<ul style="list-style-type: none"> <li>Fax from print driver</li> <li>Auto fax transmission reduction</li> <li>Page-by-page job status at the machine</li> <li>Fax from platen</li> <li>Delay start</li> <li>Automatic memory resend</li> <li>Automatic cover sheets</li> <li>Priority send</li> <li>Broadcast up to 200 recipients</li> <li>Booklet Scan</li> <li>PSTN Fax</li> <li>Internet Fax</li> <li>LAN Fax</li> </ul>
<b>Fax Receive Features</b>	<ul style="list-style-type: none"> <li>One- or two-sided printing</li> <li>Reduction at reception to fit available paper</li> <li>Junk Fax prevention</li> </ul>
<b>Fax Forward</b>	When enabled with the scan and fax kit, faxes can be received into a mailbox. Images that are in the mailbox can be routed to an Email, an FTP or SMB location or a Fax.
<b>Fax Reports</b>	<ul style="list-style-type: none"> <li>Activity report</li> <li>Dial directory</li> <li>Transmission confirmation</li> <li>Pending fax</li> <li>Mailbox</li> </ul>
<b>Fax Receive Mailboxes</b>	Up to 200 password-protected mailboxes
<b>Auto Dialing</b>	Auto redial, Batch send
<b>Single Line option</b>	<ul style="list-style-type: none"> <li>Total of 200 speed dials (single-line option)</li> <li>Up to 50 dial groups with up to 20 recipients per group (single line option)</li> </ul>
<b>Internet Fax (Optional) – Standard with One or Three line Fax option</b>	
<b>Capability</b>	<ul style="list-style-type: none"> <li>Direct document transmission to remote Internet Fax machines or email clients (SMTP)</li> <li>Reception and automatic printout of documents in black and white sent via email from remote Internet Fax machines or email clients</li> </ul>
<b>Maximum Scan Area</b>	11.7 x 17 in. /297 x 432 mm
<b>Address Directory Access</b>	Downloaded address list (comma-separated file format)
<b>File Formats</b>	TIFF-FX Profiles S, F with G3 MH, or G4 MMR
<b>Resolutions</b>	<ul style="list-style-type: none"> <li>600 x 600 dpi</li> <li>400 x 400 dpi</li> <li>200 x 200 dpi</li> <li>200 x 100 dpi</li> <li>Bit Depth: 1 bit (monochrome)</li> </ul>
<b>Network Protocols</b>	<ul style="list-style-type: none"> <li>SMTP</li> <li>POP3</li> </ul>
<b>Compliance</b>	ITU-T T.37 compliant

Copy Specifications	
<b>First-Image-Out Time – letter size, from platen to center tray</b>	
<b>Black and White</b>	As fast as 4.8 Seconds
<b>Color</b>	As fast as 6.7 Seconds
<b>Copying</b>	
<b>Document Scanner</b>	Duplex Automatic Document Feeder with 75-sheet capacity (based on 80 gsm paper)
<b>Sides (input:output)</b>	1:1, 1:2, 2:2 and 2:1
<b>Quantity</b>	1 to 999
<b>Resolution</b>	600 x 600 dpi
<b>Concurrency</b>	Concurrent scanning and printing
<b>Digital Imaging</b>	<ul style="list-style-type: none"> <li>Auto color</li> <li>Auto rotation</li> <li>Image shift</li> <li>Edge erase</li> <li>Auto centering</li> <li>Original type selection (photo and text, photo, text, map) with subtypes</li> <li>Lighter/darker</li> <li>Background suppression</li> <li>Auto and manual contrast</li> <li>Sharpness</li> <li>Color balance, color shift and saturation</li> </ul>
<b>Reduction/Enlargement</b>	<ul style="list-style-type: none"> <li>Variable zoom from 25 % to 400 % in 1 % increments</li> <li>Anamorphic zoom</li> <li>Six user-programmable percentages</li> </ul>
<b>Special Features</b>	<ul style="list-style-type: none"> <li>Auto paper select</li> <li>Auto reduction/enlargement to fit selected paper size</li> <li>Auto registration</li> <li>Auto tray switching</li> <li>Automatic job recovery</li> <li>Auto color selection</li> <li>Watermark</li> <li>Annotation</li> <li>Area Designation</li> <li>Full color</li> <li>Single/Dual color</li> <li>Copy calibration</li> </ul>



<b>Special Features (continued)</b>	<p>Booklet creation  Multi-up – 2, 4 or 8 up  Repeat image  Transparency dividers  Negative image  Mirror image  Covers insertion (front only, front and back, back only; blank or printed)  Build Job (enables special programming for different pages in one document – can be used for inserts, different paper sources, and mixing input from the document glass and the document feeder)  Store and recall job programming  Job interrupt  Bound document copying  Sample set  Mixed-size originals  Hole Punch (requires Professional Finisher or Advanced Office Finisher)  V-Folding (requires Professional Finisher)  Saddle-stitch booklets (requires Professional Finisher)  Stapling (single/dual/quad) quad requires Advanced Office Finisher or Professional Finisher  ID Card Copy</p>
<b>Foreign Device Interface</b>	<p>Interface to third-party access control devices, coin machines and card readers  Supports a variety of vending stations available through the Xerox Custom Application Service</p>
<b>Device Specifications</b>	
<b>Paper Handling – Duplex Automatic Document Feeder</b>	
<b>Capacity</b>	75 sheets (based on 80 gsm paper)
<b>Speed</b>	50 images per minute black and white / 45 images per minute color (Letter/A4 long edge feed (LEF))
<b>Paper Sizes Sensed</b>	<p>Statement – 5.5 x 8.5 in. (A5/148 x 210 mm) long edge feed (LEF) or short edge feed (SEF)  Letter – 8.5 x 11 in. (A4/210 x 297 mm) LEF or SEF  Legal – 8.5 x 14 in. (216 x 356 mm) SEF  Ledger – 11 x 17 in. (A3/297 x 420 mm) SEF  8 x 10 in. (B5/182 x 257 mm) SEF</p>
<b>Weights</b>	16 to 32 lb bond/38 to 128 gsm
<b>Paper Handling – Bypass Tray</b>	
<b>Capacity*</b>	100 sheets
<b>Sizes</b>	4.13 x 5.83 in. (A6/105 x 148 mm) to 12 x 19 in. (SRA3/320 x 450 mm)
<b>Weights</b>	16 lb bond to 80 lb Cover/55 to 220 gsm
<b>Types</b>	Same as front-loading trays plus label stock and envelopes
<b>Paper Handling – Front-Loading Paper Tray (Standard)</b>	
<b>Capacity*</b>	520 sheets
<b>Sizes</b>	User adjustable from 5.5 x 8.5 in. (A5/148 x 210 mm) to 11 x 17 in. (A3/297 x 420 mm)
<b>Weights</b>	17 to 80 lb Cover/55 to 220 gsm

\*Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.

<b>Types</b>	Plain Paper Recycled Bond Custom Type 1 through 5 Lightweight Heavyweight Extra Heavyweight Transparency Heavyweight Gloss Labels Gloss Extra Heavyweight Gloss Punched Letterhead Pre-printed Envelopes
<b>Paper Handling – Input Tray Options - Three Tray Option (Tray One and Two plus Two Tray Module)</b>	
<b>Tray 2 - Tray 4</b>	520 sheets
<b>Sizes</b>	User adjustable from 5.5 x 8.5 in. (A5/148 x 210 mm) to 11 x 17 in. (A3/297 x 420 mm)
<b>Weights</b>	17 to 80 lb Cover/55 to 220 gsm
<b>Types</b>	Plain Paper Recycled Bond Custom Type 1 through 5 Lightweight Heavyweight Extra Heavyweight Transparency Heavyweight Gloss Labels Gloss Extra Heavyweight Gloss Punched Letterhead Pre-printed Envelopes
<b>Total Capacity*</b>	2,180 sheets (Includes Tray 1, Tray 2, Trays 3-4 and Bypass Tray)
<b>Paper Handling – Input Tray Options - High-Capacity Tandem Tray Option</b>	
<b>Tray 2</b>	520 sheets
<b>Sizes</b>	User adjustable from 5.5 x 8.5 in. (A5/148 x 210 mm) to 11 x 17 in. (A3/297 x 420 mm)
<b>Tray 3 - Tray 4</b>	2,000 sheets
<b>Sizes</b>	8.5 x 11 in., B5, A4
<b>Weights</b>	17 to 80 lb Cover/64 to 220 gsm

# WorkCentre 7346

<b>Types</b>	Plain Paper Recycled Bond Custom Type 1 through 5 Lightweight Heavyweight Extra Heavyweight Transparency Heavyweight Gloss Labels Gloss Extra Heavyweight Gloss Punched Letterhead Pre-printed Envelopes
<b>Total Capacity*</b>	3,140 sheets (Includes Tray 1, Tray 2, Bypass Tray and High Capacity Feeder)
<b>Output – Center Catch Tray</b>	
<b>Stacking Tray</b>	400 sheets (Cannot be accessed with the Advanced Office Finisher or Professional Finisher attached)
<b>Sizes</b>	4.13 x 5.83 in. (A6/105 x 148 mm) to 12 x 19 in./320 x 483 mm
<b>Output – Convenience Stapler Option</b>	
<b>Capacity*</b>	Up to 50 sheets (5,000 staples per cartridge)
<b>Output – Office Finisher Option</b>	
<b>Stacking Tray</b>	1,000 sheets
<b>Sizes</b>	8 x 10 in./B5 to 11 x 17 in./A3
<b>Weights</b>	17 to 28 lb bond/64 to 105 gsm
<b>Stapling</b>	Single and dual Auto stapling (50 sheets maximum) – 20 lb/80 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported
<b>Output – Advanced Office Finisher Option</b>	
<b>Top Tray</b>	500 sheets
<b>Stacking Stapling Tray</b>	3,000 sheets
<b>Sizes</b>	8 x 10 in./B5 to 11 x 17 in./A3
<b>Weights</b>	17 to 80 lb Cover/60 to 220 gsm
<b>Stapling</b>	Single and dual Auto stapling (50 sheets maximum) – 24 lb bond/90 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported
<b>Hole Punch</b>	North America: 3 Hole Punch Europe: 2–4 Hole Punch

\*Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.

# WorkCentre 7346

Output – Professional Finisher Option	
Top Tray	500 sheets
Stacking Stapling Tray	1,500 sheets
Sizes	8 x 10 in./B5 to 11 x 17 in./A3
Weights	17 to 110 lb index/60 to 220 gsm
Stapling	Single Auto stapling (50 sheets maximum) – 24 lb/90 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported
Booklets - Booklet Tray	Saddle-stitch up to 15 sheets (One 60 lb Cover/169 gsm plus fourteen 24 lb bond/90 gsm sheets) V-fold up to 5 sheets Letter, Legal, Tabloid, A3, A4 supported
Hole Punch	North America: 3 Hole Punch Europe: 2–4 Hole Punch
Security	
Capability	Secure Print, NDS Authentication over IP, LDAP/Kerberos/SMB, Password Protected PDF, Encrypted Disk, Audit Log and Encrypted Scan to Email. Hard disk overwrite immediate or on demand. Secure Web Page via SSL. IPv6
Accounting	
Auditron	Allows for control of black and white and color usage by user by feature; copy, print, fax and scan
Xerox Standard Accounting	Tracking: Copy, Print, Fax and Scan usage Accounting: Up to 1,000 User accounts (User ID); Up to 500 General accounts (Client); Up to 750 Group accounts (Department) Features: Enable/disable via the web UI or the GUI in tools, admin can manage the feature remotely via the web UI, Data can be exported via a CSV file, user required to enter XSA ID into the print driver when submitting a print job, similar to secure print.
Color Access Via Active Directory	Allows the device to be set up so users have unlimited access to black and white copy and print functions. If a user wants to print or copy in color they must authenticate.
Accounting Control	Network accounting to enable Business Partner Solutions
Accounting with Third-Party Server Applications	Up-to-the-minute data on how the system is being used; comprehensive usage tracking and reporting; print, scan, copy and fax
Monthly Duty Cycle	
	150,000
Basic Configurations**	
	Network Multifunction System with network controller and stand Notes: Platen cover, Duplex Automatic Document Feeder is available with all configurations

Accessories				
	Three Tray Paper Feeder High Capacity Tandem Tray One-line fax with Internet Fax Three-line fax with Internet Fax Fax Server Enablement Scan Kit Thumbnail preview Secure Watermark Scan to PC Desktop (Professional or SE edition) Media Print (Print from a USB Thumb drive or media card) USB/Parallel Port Printing Office Finisher Advanced Office Finisher Professional Finisher Foreign Device Interface Convenience Stapler			
Electrical Requirements				
	220-240 V Nominal, 50/60 Hz, 10A 100-127 Vac, 50/60 Hz, 12A			
Power Consumption				
<b>Running</b>	< 1080 watts			
<b>Standby</b>	< 200 watts			
<b>Low-Power Mode</b>	< 85 watts			
<b>Sleep Mode</b>	< 10 watts			
<b>Warm Up</b>	70 seconds			
<b>Low-Power Recovery</b>	30 seconds (maximum)			
<b>Required Temperature Range</b>	50° to 82° F (10° to 28° C)			
<b>Required Relative Humidity</b>	15% to 85 %			
<b>Noise Emission</b>	28 dB(A) standby 56 dB(A) running 61 dB(A) impulse			
<b>Heat Emission</b>	3441 BTU/Hr running 683 BTU/Hr standby			
Dimensions and Weight				
	Width	Depth	Height	Weight
<b>Fully Configured</b>	73 in./1,856 mm	33 in./834 mm	46 in./1,161 mm	616 lbs/280 kg
Xerox Extensible Interface Platform™ (EIP)				
	Xerox Extensible Interface Platform (EIP) is an embedded software platform built with state of the art web technologies. This platform provides the means for software developers to quickly build solutions that are more intuitive and user-friendly for the office workers. Chief among the capabilities provided by EIP is the development of tailored applications with customized user interfaces, and card-based authentication solutions supporting a personalized user experience.			

# WorkCentre 7346

Certifications			
	FCC Class B Compliant (U.S.), DOC Class A Compliant (Canada) 89/336/EEC (Europe) UL Listed (UL60950-1, First Edition) CB Certified (IEC 60950-1/EN 60950-1) 73/23/EEC (Europe) Novell Tested and Approved Windows Hardware Quality Labs		
Supplies	Description	Order Number	
Toner Cartridges	Black	6R1175	
	Cyan	6R1176	
	Magenta	6R1177	
	Yellow	6R1178	
Staple Refills	For Office Finisher	8R12915	
	For Advanced Finisher	8R12941	Used on Advanced and Professional Finisher plus Convenience Stapler 3 refills at 5,000 each
	For Professional Finisher	8R12925	Used on Professional Finisher (Booklet Function) 4 refills at 5,000 each
Staple Cartridges	For Advanced and Professional Finishers	8R12964	Used on Advanced and Professional Finisher plus Convenience Stapler (1 cartridge)
Smart Kits			
	Smart Kit™ Drum Cartridge	13R00624	
	Smart Kit™ Waste Cartridge	008R12903	
	Smart Kit™ Fuser Module (220 V)	008R13056	
	Smart Kit™ Fuser Module (110 V)	008R13055	

