



System Specifications	WorkCentre® 6515N	WorkCentre® 6515DN	WorkCentre® 6515DNI
One-sided Speed 8.5 x 11 in. A4 / 210 x 297 mm 8.5 x 14 in. / 216 x 356 mm	Up to 30 ppm colour and black-and-white Up to 28 ppm colour and black-and-white Up to 24 ppm colour and black-and-white		
Two-sided Speed 8.5 x 11 in. A4 / 210 x 297 mm 8.5 x 14 in. / 216 x 356 mm	NA	Up to 19 ppm colour and black-c Up to 18 ppm colour and black-c Up to 17 ppm colour and black-c	ınd-white
Monthly Duty Cycle <sup>1</sup>	Up to 50,000 pages / month		
Recommended Average Monthly Print Volume <sup>2</sup>	Up to 3,000 pages		
Processor	1.05 GHz		
Memory	2 GB		
Connectivity	10/100/1000Base-T Ethernet High-Speed USB 3.0		10/100/1000Base-T Ethernet High-Speed USB 3.0 Wi-Fi 802.11n Wi-Fi Direct <sup>®</sup>
Device Specifications			
Electrical Requirements			
North Americα	Voltage: 120 VAC +/- 10 % Frequency: 60 Hz +/- 3 Hz, 12A		
Europe	Voltage: 220-240 VAC +/- 10 % Frequency: 50 Hz +/- 3 Hz, 6A		
Power Consumption			
Operation <sup>4</sup>	120V: Maximum 350 watts 220V: Maximum 370 watts		
Standby Mode <sup>4</sup>	120V: Maximum 51 watts 220V: Maximum 52 watts		
Power Off Mode <sup>4</sup>	120V: Maximum 0.2 watts 220V: Maximum 0.3 watts		
Sleep Mode <sup>4</sup>	120V: Maximum 1.1 watts 220V: Maximum 1.2 watts		
Warm-up (from Sleep Mode)	As fast as 27 seconds		
Operating Environment			
Required Temperature Range Storage Operating	-4°F to 104°F / -20°C to 40°C 41°F to 90°F / 5°C to 32°C		
Required Relative Humidity	15 % to 85 %		

Sound Power Levels Operating Standby	6.84 B or less 4.25 B or less			
Sound Pressure Levels Operating Standby	52.5 dB(A) or less 26.3 dB(A) or less			
Dimensions and Weights (unpackaged)	Width	Depth	Height	Weight
WorkCentre® 6515N, DN and DNI	16.5 in. / 420 mm	19.9 in. / 506 mm	19.7 in. / 500 mm	67.7 lb. / 30.7 kg
550-sheet Paper Tray	16.5 in. / 420 mm	18.3 in. / 465 mm	5.9 in. / 150 mm	14.8 lb. / 6.7 kg
Dimensions and Weights (packaged)	Width	Depth	Height	Weight
WorkCentre® 6510N, DN and DNI	25 in. / 634 mm	22.8 in. / 580 mm	26 in. / 659 mm	79.8 lb. / 36.2 kg
550-sheet Paper Tray	21.1 in. / 535 mm	23 in. / 584 mm	9.8 in. / 248 mm	18.7 lb. / 8.5 kg
Cortifications				

#### Certifications

To view the latest list of certifications, go to <a href="https://www.xerox.com/OfficeCertifications">www.xerox.com/OfficeCertifications</a>.

Print	
First-Print-Out Time	As fast as 12 seconds colour and black-and-white
Print Resolution	Up to 1200 x 2400 dpi
Page Description Languages	Adobe® PostScript® 3™ PCL® 5e, 6 PDF TIFF
Maximum Print Area	4 mm edge of paper
Print Features	Banner Sheets Booklet Print Cover / Separators Draft Mode Fit to Page N-up Overlays PANTONE® Colour Calibrated Solid-colour Simulations Personal Print Proof Print RAM Collation Run Black Saved Print Secure Print Watermarks
Print from USB	Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS
Operating Systems	Windows®, 7, 8, 10, Server 2000, Server 2003, Server 2008, Server 2008 R2, Server 2012  Mac OS® version 10.10 and higher  Citrix®  Redhat® Enterprise  Linux®  IBM® AIX® 5  HP-UX® 11iv2  Oracle® Solaris 9, 10  Fedora Core 12-15  SUSE®
Font Capability	136 PostScript fonts 88 PCL fonts

Xerox <sup>®</sup> Mobile Express Driver <sup>®</sup>	Makes it easy for mobile users to find, use and manage Xerox® and non-Xerox® devices in every new location. Plug into a new network, and Mobile Express Driver® automatically discovers available printers and provides status and capability information. Save a list of "favourite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.	
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for endusers, reducing the number of support calls, and simplifying print services management.	
Сору		
Document Scanner	Single-pass Duplex Automatic Document Feeder (DADF) with 50-sheet capacity	
Document Scαnner Size	Plαten: Up to 8.5 x 11.7 in / A4 DADF: 8.5 x 14 in. / 216 x 356 mm	
Simplex Speed	Black-and-White: Up to 21 cpm (copies per minute) 8.5 x 11 in. / A4 / 210 x 297 mm Colour: Up to 13 cpm (copies per minute) 8.5 x 11 in. / A4 / 210 x 297 mm	
Duplex Speed	Black-and-White: Up to 9 cpm (copies per minute) 8.5 x 11 in. / A4 / 210 x 297 mm Colour: Up to 8 cpm (copies per minute) 8.5 x 11 in. / A4 / 210 x 297 mm	
First-Copy-Out Time	As fast as 12 seconds from the platen	
Sides (input:output)	1:1, 1:2, 2:2, and 2:1	
Quantity	1 to 999	
Resolution	Up to 600 x 600 dpi	
Reduction/Enlargement	Variable zoom from 25 % to 400 % in 1 % increments	
Concurrency	Concurrent scanning and printing	
Copy Features	Automatic Background Suppression Book Copying Book Copying with Centre Erase Collation Darkness Control Edge Erase ID Card Copy N-up Reduce/Enlarge (25 % -400 %) Image Shift Original Type Sample Copy Sharpness	
Scan		
Capability	Colour and Black-and-white	
Concurrency	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs	
Input Speed - Black-and-White	Scan up to 37 ipm – 8.5 x 11 in. / A4 / 210 x 297 mm	
Input Speed - Colour	Scan up to 21 ipm – 8.5 x 11 in. / A4 / 210 x 297 mm	
Resolution	Optical – 600 x 600 dpi	
Bit Depth	24-bit Colour / 8-bit Greyscale	
Maximum Scan Area	Plαten: Up to 8.5 x 11.7 in. / A4 Document Feeder: Up to 8.5 x 14 in. / 216 x 356 mm	
Network Filing Protocol	FTP SMTP SMB/SMB2	
File Formats	JPG Single-page and Multi-page TIFF PDF Searchable PDF with integrated OCR	
Scan Driver Compatibility	WIA TWAIN	

Supported Scan Destinations	Scan to Email (local address book or LDAP integration) Scan to Network (via FTP/SMB) Scan to USB Memory Device Scan to Email (SMTP) Scan to WSD Scan to Application (TWAIN Network) Scan to WIA (WSD Scan) Scan to Mac 10.9 or later (Network/Mac ICA) Scan to Network Computer (SMB/FTP) Scan to Multiple Destinations in a Single Scan Job		
Fax <sup>5</sup>			
Fax Speed	33.6 Kbps		
Memory	4 MB		
Resolution	Up to 400 x 400 dpi		
Compression	MH/MR/MMR/JBIG		
Fax Features	Broadcast Sending (up to 200 destinations) Delayed Start (up to 24 hours) Fax Address Book (up to 200 speed dials) Fax Forward to Email Fax Forwarding and Local Print Polling Receive Reject Junk Fax Secure Fax Receive		
Mobile Solutions and Mobile Device Apps			
Apple <sup>®</sup> AirPrint <sup>®</sup>	Print email, photos and important office documents directly from an Apple iPhone <sup>®</sup> or iPad <sup>®</sup> with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.		
Google Cloud Print™	Google Cloud Print connects print devices to the web, enabling users to print the applications they use every day from smartphones, tablets, Chromebook™ notebook computers and any other webconnected device.		
Mopriα <sup>®</sup> Certified	Mopria certification ensures you can print wirelessly from your Mopria supported (Android) smart phone, tablet and other mobile devices instantly and easily.		
Xerox® Print Service Plug-in for Android™ (Free at Google Play™ Store)	The Xerox® Print Service Plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, web pages and documents when your mobile device is connected to printers or multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store.		
Xerox <sup>®</sup> Mobile Link App (Free at Google Play™ Store and Apple <sup>®</sup> App Store)	The Xerox® Mobile Link App allows you to scan, email and fax from your phone or tablet by connecting with our multifunction printers and send data to and print data from cloud storage. It is easy to create Mobile Link One-Touch Workflows between a mobile device and a multifunction printer. Using a manual address or QR code identification for pairing, automatic device discovery makes it easy to find and pair a mobile device with a nearby Xerox® multifunction printer.		
Xerox® Wireless Print Solutions Adapter (Optional)	The Xerox® Wireless Print Solutions Adapter seamlessly connects your Xerox® printer or MFP to modern mobile and desktop workflows, regardless of your office environment. For more information, visit www.xerox.com/WPSA.		
Xerox® Workplace Suite and Xerox® Workplace Cloud	Xerox® Workplace Solutions boost productivity and reduce costs with a modular print management and mobility solution. Control and manage your printer fleet while enabling mobile productivity with simplified workflows, convenience and security — for any brand printer, anywhere. Xerox® Workplace Solutions offer flexible license options to suit any size business with the ability to scale as you grow.  • Xerox® Workplace Suite: On-site, your server  • Xerox® Workplace Cloud: Simple setup, cloud administration To learn more about the Xerox® Workplace Suite and Xerox® Workplace Cloud, visit www.xerox.com/Mobility.		

Security	
Security Features	Simultaneous HTTP and HTTPS support IPsec 802.1x Authentication S/MIME IP Filtering Secure Print Secure Fax Receive SNMP v3 LDAP (SASL) Network Authentication Kerberos Authentication (Unix / Linux / Windows ADS)
Paper Handling	
Document Feeder	
Capacity <sup>3</sup>	Single-pass Duplex Automatic Document Feeder (DADF): 50 sheets
Sizes	Custom Sizes: 5.5 x 5.5 in. to 8.5 x 14 in. / 139.7 x 139.7 mm to 216 x 356 mm
Weights	16 lb. bond to 45 lb. cover / 60 to 125 gsm
Bypass Tray	
Capacity <sup>3</sup>	50 sheets
Sizes	Custom Sizes: 3 x 5 in. to 8.5 x 14 in. / 76 x 127 mm to 216 x 356 mm
Weights	16 lb. bond to 58 lb. cover / 60 to 220 gsm
Mediα Types	Bond Plain Cardstock Custom Envelopes Glossy Cardstock Hole Punched Labels Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Preprinted Recycled
Tray 1	
Capacity <sup>3</sup>	250 sheets
Sizes	Custom Sizes 3 x 5.8 in. to 8.5 x 14 in. / 76 x 147 mm to 216 x 356 mm
Weights	16 lb. bond to 65 lb. cover / 60 to 176 gsm
Mediα Types	Bond Plain Cardstock Custom Envelopes Glossy Cardstock Hole Punched Labels Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Preprinted Recycled
Optional Tray 2	
Capacity <sup>3</sup>	550 sheets
Sizes	Custom Sizes: 3 x 7.5 in. to 8.5 x 14 in. / 76 x 191 mm to 216 x 356 mm
Weights	16 lb. bond to 65 lb. cover / 60 to 176 gsm

	I		
Mediα Types	Bond Plain Cardstock Custom Glossy Cardstock Hole Punched Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Preprinted Recycled		
Total Capacity			
Device Standard Capacity <sup>3</sup>	300 sheets		
Device Total Capacity <sup>3</sup>	850 sheets		
Paper Output			
Output Capacity <sup>3</sup>	150 sheets		
Automatic 2-Sided	NA	Standard	
Device Management			
Network Protocols	TCP/IP: HTTP/HTTPS, IPP, LPR/LDP, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD SMB SMTP, Secure SMTP LDAP, Secure LDAP Bonjour® / AirPrint® FTP Most protocols not in use can be disabled		
Administrative Protocols	DHCP, SNMP v2/3, WINS, DHCP A	utonet, TLS, SNTP, MDNS	
Xerox® CentreWare® Web			
	<ul> <li>A web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system</li> <li>Works with any SNMP-managed printer from any manufacturer</li> <li>Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management</li> </ul>		
Xerox® Embedded Web Server - In	ntegrated Device Web Page		
Device Status	<ul> <li>Tray Status / Contents</li> <li>Consumables Status</li> <li>Billing / Usage</li> <li>Quick Links</li> </ul>		
Job Submission	Print-ready files (PS, PCL®, PDF, XPS, JPEG)		
Device Administration	Allows simple, remote installation setting of configuration options and management of the device.		
Browsers	Microsoft® Internet Explorer 11 Microsoft Edge™ 38 Mozilla™ Firefox® 48 Apple® Safari® 9.1 Google Chrome™ 52		
Remote Print Services			
Xerox <sup>®</sup> Automated Meter Readings (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.		
Xerox® Automatic Supplies Replenishment (ASR)	Automatically orders supplies for Xerox <sup>®</sup> output devices based on actual usage, eliminating the need to manually manage supplies inventory.		
Troubleshooting and Diagnostic Support	Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting/repair process. Diagnostic data is sent to Xerox, allowing for problems to be solved faster with increased uptime.		

What's In The Box	
	<ul> <li>WorkCentre® 6515 Colour Multifunction Printer</li> <li>Standard Capacity Print cartridge: One of each (Cyan, Magenta, Yellow): 1,000 print capacity<sup>6</sup>; Black: 1,500 print capacity<sup>6</sup></li> <li>Software and Documentation CD (with User Manual, Quick Install Guide, Safety, Regulatory, Recycling and Disposal Guides, Print Drivers, and Warranty Statement)</li> <li>Installation Guide</li> <li>Quick Use Guides</li> <li>Power Cord</li> <li>Fax Cord</li> </ul>

Supplies and Accessories	Quantity	Part Number
Supplies		
Extra-High Capacity Print Cartridges	Cyan: 4,300 standard pages <sup>6</sup> Magenta: 4,300 standard pages <sup>6</sup> Yellow: 4,300 standard pages <sup>6</sup>	106R03693 106R03694 106R03695
High Capacity Print Cartridges	Black 5,500 standard pages <sup>6</sup> Cyan: 2,400 standard pages <sup>6</sup> Magenta: 2,400 standard pages <sup>6</sup> Yellow: 2,400 standard pages <sup>6</sup>	106R03488 106R03485 106R03486 106R03487
Standard Capacity Print Cartridges	Black: 2,500 standard pages <sup>6</sup> Cyan: 1,000 standard pages <sup>6</sup> Magenta: 1,000 standard pages <sup>6</sup> Yellow: 1,000 standard pages <sup>6</sup>	106R03484 106R03481 106R03482 106R03483
Drum Cartridges	Black: 48,000 pages <sup>7</sup> Cyan: 48,000 pages <sup>7</sup> Magenta: 48,000 pages <sup>7</sup> Yellow: 48,000 pages <sup>7</sup>	108R01420 108R01417 108R01418 108R01419
Waste Cartridge	30,000 pages <sup>7</sup>	108R01416
Accessories		
550-sheet Paper Tray		097S04765
Wireless Network Adapter		497K16750
Cabinet (includes Caster Base)		097S04994

<sup>&</sup>lt;sup>1</sup> Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling programme. For more information, visit http://www.xerox.com/About-Xerox/Recycling.

For more information, visit us at www.xerox.com.



Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.

Power states defined per ENERGY STAR® Programme requirements for Imaging Equipment.

Requires analogue phone line.

Average standard pages. Declared Yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage and print

Approximate pages. Declared Yield based on letter-/A4-size 20 lb. (75 gsm) pages. Yield will vary based on media type, size, weight, orientation, and usage patterns.